

# ROTARY EVAPORATOR

## ALS-INS035



**Registered Office:** 43-B, 3<sup>rd</sup> Floor, Okhla Village Jamia Nagar, New Delhi - 110025, India.

**E-mail :** instruments@almanaclife.com | **Web :** www.almanaclife.com

**Landline No:** 011-43506838 | **WhatsApp No:** +91 9773645708

## DESCRIPTION

Our Rotary Evaporator ALS-INS035 is a vital instrument in chemical laboratories, designed to efficiently and gently remove solvents from samples through controlled evaporation. It operates under reduced pressure, which lowers the boiling point of solvents, allowing for their removal at lower temperatures and thereby protecting thermally sensitive compounds. The applications are in Chemical & Pharmaceutical Industry, Food & Beverage Industry, Cannabis & Botanical Extracts, Environmental & Analytical Laboratories and Materials Science & Nanotechnology.

## FEATURES

### **Clear LCD Temperature Display**

The rotary evaporator features a clear LCD that provides accurate and immediate temperature readings during operation. This precise monitoring allows users to maintain optimal conditions and quickly adjust settings for consistent performance.

### **Brushless DC Motor**

The device is powered by a DC brushless motor, known for its high efficiency, smooth performance, and low maintenance requirements. This motor type contributes to reduced noise levels and enhanced durability, ensuring reliable long-term operation in the laboratory.

### **Reversible Direction of Rotation of Sample Flask**

The reversible rotation feature of the sample flask ensures that the contents are evenly exposed to the heating surface, promoting uniform temperature distribution and efficient evaporation. This capability not only improves the consistency of the sample processing but also enhances overall experimental reproducibility and performance.

### **Permissible Ambient Temperature Range (5°C to 40°C)**

The device is engineered to operate reliably within an ambient temperature range of 5°C to 40°C, ensuring effective performance in varied laboratory environments. This flexibility minimizes thermal stress on the equipment and maintains operational stability even under fluctuating environmental conditions.

### **Optimal Function in High Humidity (Up to 80% Relative Humidity)**

Designed to perform optimally in environments with relative humidity levels up to 80%, the evaporator is well-suited for use in humid laboratory settings. This capability reduces the risk of moisture-related issues, such as condensation or corrosion, thereby ensuring consistent and dependable operation.

### **Material of Construction (MOC)**

The rotary evaporator is constructed using Mild Steel (MS) powder-coated metallic sheets, providing a robust, cost-effective, and corrosion-resistant framework. Borosilicate IP20/IP21 grade glass is employed for its excellent chemical resistance and thermal stability, ensuring the safe handling of various solvents and chemicals during operation.

## CONTROLLER FEATURES

- Up/Down Key (Height Adjustment):** These keys, control the vertical movement of the rotary evaporator's main assembly or the flask above the heating bath.
- Speed Button and Knob (Maximum 280 rpm):** Rotating this knob sets the rotational speed of the flask, with a maximum of 280 rpm.
- Temperature Button and Knob (Maximum 180°C):** Pressing the temperature button activates temperature setting mode, after which the knob can be rotated to the desired temperature, up to 180°C.
- Timer Button (Maximum 999 Minutes):** This button allows the user to set a specific duration for the evaporation process, up to 999 minutes.
- Interval Button (Reversible Rotation):** By pressing the interval button, you can define how often the direction of the flask rotation will reverse (e.g. every 5 seconds). Alternating clockwise and counterclockwise rotations helps distribute heat more uniformly, particularly useful for samples that may settle or require thorough agitation

### TECHNICAL SPECIFICATION

Model	ALS-INS035RE
Motor Type	Brushless DC motor
Speed Range	20-280 rpm
Display	LCD (speed, temperature, time)
Clockwise and Anti-clockwise	Yes
Heating Temperature Range	Room temp. to 180°C
Control Accuracy	±1°C
Heating Power	1300 W
Stroke Displacement	Automatic 150 mm
Timer	Yes
Time Setting Range	1-999 min
Dimension [DxWxH]	465 × 457 × 583 mm
Weight	15 kg
Additional Weight	2.8 kg
Protection Class	IP20/IP21
USB Interface	Yes
Voltage/Frequency	100-120/200-240V 50/60 Hz
Power	1400 W