

THERMOSHAKER INCUBATOR

ALS-INS041



Registered Office: 43-B, 3rd Floor, Okhla Village Jamia Nagar, New Delhi - 110025, India.

E-mail : instruments@almanaclifescience.com | **Web :** www.almanaclifescience.com

Landline No: 011-43506838 | **WhatsApp No:** +91 9773645708

DESCRIPTION

THERMOSHAKER INCUBATOR ALS-INS041 is a comprehensive upgrade to the existing instruments. Different from the common setting of instrument parameters through poly domes, it uses a 4.3-inch color LCD screen combined with a graphical operation interface to give users a better experience. Various program editing options, such as shaking start time, cycle steps, heating rate, etc., help to find the best experimental conditions.

FEATURES

- Microprocessor control, good temperature control linearity, accurate shaking speed, small fluctuation
- DC brushless motor drive, long service life, maintenance-free
- Excellent performance, precise temperature control
- Full power heating can be selected, and the highest 3 °C/min heating method can also be selected to prevent the experiment from failing due to uneven temperature changes
- Optional thermos lid accessories, effectively improve the temperature uniformity in the test tube
- Optional full power cooling, or up to 1°C/min cooling
- Multiple block choices, faster block loading and unloading
- Various blocks are available, and can be customized
- New designed method of block loading and unloading, blocks can be replaced without tools
- Open design, more comprehensive program setting
- Various heating methods, you can choose the appropriate method according to the experimental needs
- The shaking method can be set according to requirements, and both forward and reverse rotation can be set
- Program continuous operation function, multiple programs are connected to each other, no need to set repeatedly
- 4.3-inch color LCD screen display, intuitive and easy to operate.
- Power failure self-recovery function, the device can automatically resume.
- Operation according to the original set procedure after power failure recovery
- Various standard sample blocks are available, and the blocks can be automatically identified
- The instrument will be equipped with a mobile phone APP for real-time monitoring of instrument status

TECHNICAL SPECIFICATIONS

Model	ALS-INS041TI
Display	4.3 inch touch screen (capacitive type)
Temperature control range	RT +5°C~105°C
Temperature uniformity	≤0.5°C
Timer range	1min~99h59min
Temperature control accuracy	±0.5°C(@30-50°C)
Display accuracy	±0.1°C
Shaking speed	200-3000rpm
Heating time (25-100°C)	≤15min (RT 20°C~30°C)
Heating rate gear	Max; 3°C/min; 2°C/min; 1°C/min; 0.1°C/min
Program number	50
External port	USB: program related, printer; 7Pin socket: thermo lid
Shaking amplitude	3mm
Dimension(mm)	318x154x220
Blocks	0.5ml tubes, 2ml tubes & 96 well PCR Plate Optional: 0.2 1.5, 5, 15, 50 ml tubes, 384 well plates
Weight	10kg